

Calconduit™

Rigid Conduit, Rigid & EMT Fittings

Galvanized Rigid Conduit Elbows - 90°

Application:

Galvanized Rigid Conduit (GRC) Elbows are to be installed on conduit raceways for underground stub-ups, and interconnection of conduit runs and other fittings.

Features:


Fabricated from UL listed hot-dipped galvanized rigid conduit
Threaded ends (NPT)

Certifications and Compliances:

- UL & CUL Listed - UL6
- UL File Number E226472
- UL6 with statements of conformance
- ANSI C80.1
- CalTrans Specification 86-2.05
- A.R.R.A. Available
- ASTM A239

Options:

Available in any degree of bend from 5° to 90°, and special radius



*All dimensions are for informational purposes only
Tolerances +/-5%

Item Number	Description	Weight (lbs.)	Box Qty	A	B	C	Cut Length
ST0590EL00	1/2" X 90°	1.00	50	4.0	6.9	2.9	12.0
ST0790EL00	3/4" X 90°	1.30	50	4.5	7.4	2.9	12.9
ST1090EL00	1" X 90°	2.10	25	5.8	8.7	3.0	15.0
ST1290EL00	1-1/4" X 90°	3.40	20	7.3	10.6	3.3	18.0
ST1590EL00	1-1/2" X 90°	4.80	15	8.3	11.9	3.6	20.3
ST2090EL00	2" X 90°	7.30	10	9.5	13.8	4.3	23.4
ST2590EL00	2-1/2" X 90°	13.90	50	10.5	15.8	5.3	27.0
ST3090EL00	3" X 90°	21.30	35	13.0	18.8	5.8	32.0
ST3590EL00	3-1/2" X 90°	27.00	35	15.0	21.8	6.8	37.0
ST4090EL00	4" X 90°	36.80	35	16.0	23.1	7.1	39.3
ST5090EL00	5" X 90°	70.00	bulk	24.0	35.2	11.2	60.0
ST6090EL00	6" X 90°	111.80	bulk	30.0	42.6	12.6	72.3

Calconduit

12021 Woodruff Ave., Downey, CA 90241

Ph: (562) 803.4388 Ph: (800) 225.7473 Fax: (562) 803.4488 | calconduit.com

